



# PRESCHEM INTERIOR CLEAR

## TECHNICAL DATA SHEET

Date	Jun 04
Issue	005

TDS 03  
page 1 of 2

### DESCRIPTION

Interior Clear is a blend of penetrating natural Tung Oil and Resin. Interior Clear will provide internal timbers with a natural oiled appearance and low build seal protection. It is a non-film forming finish that does not give timber an artificial, plastic look. Interior Clear is formulated from naturally occurring drying oils, including Tung Oil which are completely safe to use on all internal wood work including bench tops, chopping boards etc. Interior Clear will not create a high gloss surface coating like urethanes, instead it offers subtle seal protection whilst nourishing the timber.

### RECOMMENDED USES

Interior Clear can be used where ever a clear, protective interior finish is required eg. paneling, flooring, bench tops, architrave's, doors and windows. Interior Clear is suitable for all popular timbers including Cedar, Jarrah, Baltic Pine, Huon Pine, Cypress Pine and Oregon. It can easily be tinted to any desired colour using commercially available pigments (oil based)

### DIRECTIONS FOR USE

Ensure a clean dry surface, free from dirt, grease and wax. Sanding of the surface is recommended unless the natural sawn timber look is being maintained. Sand the timber before application, finishing off with a fine paper, ensuring the dust is removed prior to oiling. Brush, roll or spray one generous coat well into the timber and allow at least 24 hours drying. Differences may occur with surface absorption due to the natural features of the timber porosity. It is very important to wipe off any excess oil after 1-2 hours. 2 coats is only recommended if a glossier appearance is required on the timber surface. Light sanding is recommended between coats.

---

#### Head Office

147-149 Herald St. Cheltenham Vic. 3192  
Telephone: (03) 9532 0679 Fax: (03) 9532 1041

*"Manufactures of Wood Preservatives and Clear Timber Finishes"*

---

Date	Jun 04
Issue	005

TDS 03  
page 2 of 2

## **RESTORATION**

If the timber looks dry or the timber is being soiled due to lack of sealing simply reapply another coat. Sanding and cleaning of the surface is recommended prior to this application. To obtain a higher gloss level over the Interior Clear we recommend using a timber polish. Allow around 1 week after oiling before applying timber polishes.

## **COVERAGE**

Approximately 12m<sup>2</sup>/litre on dressed timber and 8m<sup>2</sup>/litre on sawn timber.

## **CLEAN UP**

Clean applicators thoroughly with mineral turpentine.

## **PACKAGING**

Interior Clear is available in 1, 4 and 20 litres.

**TECHNICAL DATA** Flashpoint: Above 65°C (Abel Closed Cup)  
Colour: Very pale amber  
Sheen: Satin  
Density: 0.960 at 20°C  
Viscosity: 21.0mm/s (cSt) at 20°C

## **Manufactured By**

**PRESCHEM Pty. Ltd.** (A.C.N. 006 867 929)  
147-149 Herald Street, Cheltenham, Victoria 3192

*"Manufacturers of wood preservatives and clear timber finishes"*